



Gazpromneft Diesel Prioritet 10W-30, 10W-40, 15W-40 ***All-weather multigrade engine oils***

DESCRIPTION

All-weather semi-synthetic multigrade Gazpromneft Diesel Prioritet 10W-30, 10W-40 and mineral Gazpromneft Diesel Prioritet SAE 15W-40 engine oils are blended from advanced base stocks and thoroughly selected additives. Improved base oil selection provides extended service life, reduced oil consumption through burning and enhanced resistance to corrosion.

Developed in accordance with EURO 3 emission standard this range of oils substitutes API CG-4, CF-4 oils. The products are recommended for use for mixed automotive parks containing diesel medium and heavy-duty trucks as well as vehicles with gasoline engines.

BENEFITS

- Viscosity-temperature dependence improved by high viscosity index of base oils ensures stable viscosity, excellent lubrication and cooling capacity over a wide range of loads and ambient temperatures
- Enhanced thermal and oxidation stabilities extend life of oil and engine and guarantee its required performance
- High performance additives and improved base oils (with low evaporation level and reduced sulphur content) deliver maximum protection against corrosion and excellent high-temperature deposit control under severe operating conditions
- Protect engine components from wear and prevent cylinder polishing

APPLICATIONS

- Heavy-duty diesel engines, turbocharged or not, without diesel particulate filter (DPF), in trucks, buses, tractors and special vehicles, including off-road machinery produced by leading European and U.S. manufacturers, as well as trucks by KAMAZ, MAZ and other domestic OEMs.
- Gasoline engines requiring API SL oils.

SPECIFICATIONS AND APPROVALS

Gazpromneft Diesel Prioritet engine oils comply with/approved by:

- API CH-4/SL; ACEA E7, A3/B3
- MB 228.3, MAN M3275-1
- Volvo VDS-3, MTU cat.2
- Renault Trucks RLD/RLD-2, Cummins CES 20076/77
- Caterpillar ECF-1a; Komatsu KES 07.851.1
- KAMAZ, JSC (Euro 3), Avtodizel, JSC YAMZ, Russian Association of Automotive Engineers



TYPICAL PROPERTIES

<i>Typical Properties</i>	<i>Gazpromneft Diesel Prioritet 10W-30</i>	<i>Gazpromneft Diesel Prioritet 10W-40</i>	<i>Gazpromneft Diesel Prioritet 15W-40</i>
Viscosity, cSt @ 100 °C	12.0	14.5	14.5
Flash Point, COC, °C	224	221	227
Pour Point, °C	-40	-40	-35
Base Number, mg KOH/g	9.0	9.0	9.0
Sulphated Ash, %	1.3	1.3	1.3
Density @ 20 °C, g/cm ³	0.877	0.875	0.884

HEALTH AND SAFETY

When used as directed, Gazpromneft Diesel Prioritet oils have no adverse effects either on health or environment. Beyond normal hygiene no special precautions are required. Avoid contact with skin. Wear protective gloves. In case of contact, flush immediately with water and soap. For more information please refer to the Safety Data Sheet.

REDUCED ENVIRONMENTAL IMPACT

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.