

ULTRADEG 65 SPRAY

DEGREASING AGENT

DESCRIPTION

ULTRADEG 65 SPRAY is a mixture of synthetic hydrocarbons. The product is colourless, transparent and has a neutral odour. It is an all-terrain cleaner that easily removes dirt, oil, grease and resin, always used at room temperature.

APLICACION

ULTRADEG 65 SPRAY is used for cleaning and degreasing engines, landing gear, machinery, tools, etc. The product is also used to degrease industrially manufactured components. Contains no aromatic substances, chlorine or HCFCs.

ULTRADEG 65 SPRAY has been specially formulated to evaporate without leaving any residue.

PROPERTIES

ULTRADEG 65 SPRAY is highly volatile (Evaporation rate 100 / In reference to ethyl ether 1). The product leaves no residue as it is based on a mixture of specially selected synthetic solvents.

INSTRUCTIONS FOR USE

Keep the bottle upright during storage and use.

CERTIFICATIONS

NSF C1 – Register nº 158913
Halal Certificate, nº IH-682/2.4/B/76/5/1



TECHNICAL CHARACTERISTICS

Characteristics of concentrated	Units	Typical values	Method
Appearance	-	Transparent, colorless	-
Density at 15 °C	kg/dm ³	0,76	ASTM D 1298
Viscosity at 40 °C	cSt	1,0	ASTM D 445
Pour point	°C	< -23	ASTM D 97

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support.
COGELSA is not liable for damages caused by improper use of the product.

ULTRADEG 65 SPRAY

DEGREASING AGENT

HANDLING AND STORAGE

Handling not subject to special requirements. Throughout the lifespan of the product:

- Store separately from other lubricants, chemicals or foodstuffs.
- Protect from sunlight or other heat sources.
- Store at temperatures from 1°C up to +40°C.
- Keep container closed after opening.

The expiry date is 60 months from date of manufacture.

For further information and more product details, packaging and safety data sheets, please refer to our website www.cogelsa.com or contact us at: info@cogelsa.com or export@cogelsa.com

Rev: 11/22

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support.

COGELSA is not liable for damages caused by improper use of the product.

COMPANÍA GENERAL DE LUBRICANTES, S.A.
C/ Comercio, 36 P.I. Can Sunyer
08740 Sant Andreu de la Barca, Barcelona, Spain
Telf. +34 93 682 22 20 Fax. +34 93 682 00 55
comercial@cogelsa.com

Export:
Telf. +34 93 635 60 50
export@cogelsa.com

www.cogelsa.com

