

SILICON SPRAY

FOOD GRADE SILICONE SPRAY

DESCRIPTION AND APPLICATIONS

Silicone specially formulated in aerosol to obtain the maximum yield in:

- Release of all types of plastics and rubbers.
- Anti-adherent for weld.
- Anti-adherent of general use.
- Polishing of ceilings of vinyl, etc.

QUALITY LEVEL

- NSF H1 – Suitable for incidental contact with foods. Certified with registration number 153424.
- Certified HALAL nº IH-682/2.4/B/76/1/4



PROPERTIES

- Ultra fine spraying that allows a perfect control in the application of the product.
- It covers totally all types of moulds, reaching all the corners.
- It improves the finishing.
- It reduces the problems of marks and product migrations.
- It can be used in any type of plastic and rubber.

INSTRUCTIONS FOR USE

Shake energetically before use. Keep the bottle vertically, as much during the storage as when using it. Pulverize from about 30 cm. distance on the surface to treat.

TECHNICAL CHARACTERISTICS

	Method	Typical values	Units
Apearance	-	Colorless and clear	-
Density at 15 °C	ASTM D 4052	0,97	gr/cm ³
Viscosity at 40°C	ASTM D 7042	220	cSt
Flash point	ASTM D 92	310	°C
Pour point	ASTM D 97	- 42	°C

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.

SILICON SPRAY

FOOD GRADE SILICONE SPRAY

HANDLING AND STORAGE

Handling not subject to special requirements. Throughout the lifespan of the product:

- Store separately from other lubricants, chemicals or foodstuffs.
- Protect from sunlight or other heat sources.
- Store at temperatures from 1°C up to +40°C.
- Keep container closed after opening.

The expiry date is 60 months from date of manufacture.

For further information and more product details, packaging and safety data sheets, please refer to our website www.cogelsa.com or contact us at: info@cogelsa.com or export@cogelsa.com

Rev: 03/25

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support. COGELSA is not liable for damages caused by improper use of the product.

COMPAÑIA GENERAL DE LUBRICANTES, S.A.
C/ Comercio, 36 P.I. Can Sunyer
08740 Sant Andreu de la Barca, Barcelona, Spain
Telf. +34 93 682 22 20 Fax. +34 93 682 00 55
comercial@cogelsa.com

Export:
Telf. +34 93 635 60 50
export@cogelsa.com

www.cogelsa.com

