

## ULTRALUB EV 11 PC

### VANISHING LUBRICANT FLUID

#### DESCRIPTION

**ULTRALUB EV 11 PC** is formulated with hydrocarbons and food grade additive.

#### APPLICATIONS

The main application of **ULTRALUB EV 11 EP** is as lubricant for paper cup machines in the production of hot and cold beverage cups. It can cover sizes from 85 grams to more than 1 Kg and speed round shapes up to 230 cups/min.

#### PROPERTIES

- High oxidation resistance.
- Excellent load capacity of lubrication film.
- Silicone free.

#### CERTIFICATIONS

**NSF H1**, suitable for incidental food contact – n° 167798  
**Halal** Certificate, in process



#### TECHNICAL CHARACTERISTICS

	Units	Typical values	Method
Appearance	-	Clear liquid	-
Density at 15 °C	kg/L	0,84	ASTM D 1298
Viscosity at 40°C	cSt	<50	ASTM D 445
Pour point	°C	<-15	ASTM D 97
Flash point	°C	>65	ASTM D 92

#### HANDLING AND STORAGE

Handling not subject to special requirements. Throughout the lifespan of the product:

- Store separately from other lubricants, chemicals or foodstuffs.
- Protect from sunlight or other heat sources.
- Store at temperatures from 1°C up to +40°C.
- Keep container closed after opening.

The expiry date is 24 months from date of manufacture.

For further information and more product details, packaging and safety data sheets, please refer to our website [www.cogelsa.com](http://www.cogelsa.com) or contact us at: [info@cogelsa.com](mailto:info@cogelsa.com) or [export@cogelsa.com](mailto:export@cogelsa.com)

Rev: 05/23

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support.

COGELSA is not liable for damages caused by improper use of the product.