

ULTRALUB EV 6 ATOX

VANISHING OIL FOR METAL FORMING

DESCRIPTION

ULTRALUB EV 6 ATOX is a clear odorless oil, chlorine free, based in vanishing hydrocarbons and a selected content of synthetic lubricant additives.

ULTRALUB EV 6 ATOX meets completely the health and safety standards, because the product doesn't produce mist and skin, eyes or throat irritation.

ULTRALUB EV 6 ATOX may be used as MQL lubricant in aluminium cutting processes, when a completely dry piece is needed. It can be applied by spray, dropping, roller, brush, etc.

It is fully compatible with enameled, varnished or paint sheet. Due to its NSF approval, the product is specially recommended for manufacture of tin-plated, steel and aluminium cans for food industry.

APLICACIONES

ULTRALUB EV 6 ATOX has been specially developed for stamping processes where degreasing processes must be avoid. **It doesn't leave any residue.**

ULTRALUB EV 6 ATOX is recommended for metal forming, drawing and stamping of all kind of non ferrous metals: aluminium, tin, galvanized, yellow metals, etc.

CERTIFICATIONS

NSF H1, suitable for incidental food contact – nº 153962

Halal Certificate, nº IH-682/2.4/B/76/2/8

Kosher Certificate



TECHNICAL CHARACTERISTICS

	Units	Typical values	Method
Appearance	-	Clear, colorless	-
Density at 15 °C	kg/L	0,82	ASTM D 1298
Viscosity at 40°C	cSt	2,1	ASTM D 445
Flash point	°C	> 90	ASTM D 92
Vapor pressure at 20 °C	kPa	< 0,01	

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support.

COGELSA is not liable for damages caused by improper use of the product.

ULTRALUB EV 6 ATOX

VANISHING OIL FOR METAL FORMING

HANDLING AND STORAGE

Handling not subject to special requirements. Throughout the lifespan of the product:

- Store separately from other lubricants, chemicals or foodstuffs.
- Protect from sunlight or other heat sources.
- Store at temperatures from 1°C up to +40°C.
- Keep container closed after opening.

The expiry date is 48 months from date of manufacture.

For further information and more product details, packaging and safety data sheets, please refer to our website www.cogelsa.com or contact us at: info@cogelsa.com or export@cogelsa.com

Rev: 11/23

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support.

COGELSA is not liable for damages caused by improper use of the product.

COMPANÍA GENERAL DE LUBRICANTES, S.A.
C/ Comercio, 36 P.I. Can Sunyer
08740 Sant Andreu de la Barca, Barcelona, Spain
Telf. +34 93 682 22 20 Fax. +34 93 682 00 55
comercial@cogelsa.com

Export:
Telf. +34 93 635 60 50
export@cogelsa.com

www.cogelsa.com

