


Talusia Optima

High BN cylinder lubricant
for residual fuels.



APPLICATIONS	FEATURES AND BENEFITS
A premium single oil solution designed to lubricate 2-stroke engines using fuels ranging from 0.0%S up to 2.5%S.	The innovative chemistry and formulation of Talusia Optima uses high quality calcium detergents for cleanliness and in combination with Ash Free Neutralising Molecules (ANM) has proven to exceed the performance of conventional BN 100 lubricants.
All 2-stroke diesel engines running with the widest range of fuels.	Its wide sulfur operational range means it can be used with fuels of any sulfur content, which avoids embarking several cylinder lubricants and switching between them.
Particularly fit for purpose for vessels requiring regular fuel changeover.	Superior performance supports the optimisation of Lube Oil Feed Rates and maintenance costs, saving time and money.
Especially useful for engines where advanced deposit or corrosion control is needed.	Improved anti-wear performance and overall flexibility make for wider operational safety margins.

SPECIFICATIONS AND APPROVALS			
✓	Everlence (MAN B&W)	✓	Japan Engine Corporation (UE Engines)
✓	WinGD (Wärtsilä)		

TECHNICAL DATA : TALUSIA Optima			
CHARACTERISTICS	METHODS	UNITS	TYPICAL VALUES*
S.A.E. Grade	—	—	50
Density at 15°C	ISO 3675	kg/m ³	930
Kinematic Viscosity at 100°C	ISO 3104	mm ² /s	19.5
Flash Point (COC)	ASTM D 92	°C	> 230
Pour Point	ISO 3016	°C	+ 3
BN	ASTM D 2896	—	100

*The specifications above are for illustrative purposes and communicated for information only.

CUSTOMER BENEFITS

✓	Innovative formulation using Ashfree Neutralizing Molecules (ANM).
✓	Faster and more efficient acid neutralization.
✓	Better engine cleanliness.
✓	Improved thermal resistance.
✓	Outstanding deposit control including when operating with low sulfur fuels.

GENERAL RECOMMENDATIONS

COMPATIBILITY

Compatible with generally available cylinder lubricants.

Please consult your Lubmarine Lubrication Engineer should you have any questions.

STORAGE

This product should be stored under cover in clean, dry conditions and protected from frost.

Recommended storage temperature range is 5°C to 50°C.

Drums that are stored on deck should be raised on pallets and covered to protect from the elements.

Always check regularly for leakage.

COMPLIMENTARY PRODUCTS AND SERVICES

✓	Atlanta Marine D 3005 – Crankcase lubricant for 2-stroke crosshead engines.
✓	WT Supra – Innovative and environmentally friendly cooling system inhibitor concentrate.
✓	LubDiag – Engine Monitor / Engine Optimize – Comprehensive cylinder oil scrape down analysis examining the cylinder lubrication of the 2-stroke engine.
✓	LubDiag – Oil Analysis – Laboratory based used oil analysis program.
✓	LubInsight – Suite of onboard testing kits.

